



- Using CMOS IC, high reliability and stability
- 6 timing series available (A, B, C, D, E, F), from 1sec to 60hrs (H3Y-2□, H3Y-2L□, H3Y-4□)
- Flicker Relay can select by DIP switch (H3Y-2□, H3Y-2L□, H3Y-4□)
- Wide variety of time ranges (1sec to 60hrs) (H3Y-2, H3Y-2L, H3Y-4)
- Two output contacts (H3Y-2, 2□, H3Y-2L, 2L□) or Four output contacts (H3Y-4, 4□)
- Bi-Color LED provides status indication for power ON and time UP
- Compatible with MY2, MY4, LY2 relay socket
- Use adapter (Type Y-20) for flush mount

SPECIFICATIONS

DIMENSIONS(mm)		28H×22W×55D		
MODEL		H3Y-2/H3Y-2L/H3Y-4		H3Y-2□/H3Y-2L□/H3Y-4□
FULL TIME RANGE		SEC : 1, 3, 6, 10, 30, 60 MIN : 3, 6, 10, 30, 60 H R : 3, 6, 10, 30, 60		A: 1S, 10S, 1M, 10M B: 3S, 30S, 3M, 30M C: 6S, 60S, 6M, 60M D: 1M, 10M, 1H, 10H E: 3M, 30M, 3H, 30H F: 6M, 60M, 6H, 60H
RATED VOLTAGE		DC(V):12, 24, 48, 110 AC(V):12, 24, 48, 110, 220, 240 50/60Hz		
INDICATOR OPERATING		ON-Green UP-Red		
o/p C O N T A C T	MODE	H3Y-2/H3Y-2□	H3Y-2L/H3Y-2L□	H3Y-4/H3Y-4□
	TIME LIMIT 1C			
	TIME LIMIT 2C	5A 250VAC Resistive Load	10A 250VAC Resistive Load	5A 250VAC Resistive Load(4C)
	INSTANTANEOUS 1C			
L I F E	MECHANICAL	5×10 ⁶ times		
	ELECTRICAL	10 ⁵ times		
RESET TIME		0.1 sec max		
CONSUMED POWER		2VA		
AMBIENT TEMPERATURE		-10°C~+55°C		
AMBIENT HUMIDITY		45~85%RH		
WEIGHT		Approx. 45g		

CONNECTION DIAGRAMS & TIMING CHARTS

	<p>H3Y-2, H3Y-2□ ON DELAY TIMER</p>	<p>H3Y-2□ FLICKER RELAY</p>
	<p>H3Y-2L, H3Y-2L□ ON DELAY TIMER</p>	<p>H3Y-2L□ FLICKER RELAY</p>
	<p>H3Y-4, H3Y-4□ ON DELAY TIMER</p>	<p>H3Y-4□ FLICKER RELAY</p>

DIMENSIONS

Surface Mounting (N Type) : Using PYF08A, PYF08A-E, PTF08A, PTF08A-E, PYF14A, PYF14A-E Socket

Flush Mounting (Y Type) : Using Y-20 Adapter+PYF08A, PYF08A-E, PTF08A, PTF08A-E, PYF14A, PYF14A-E Socket

<p>Kaohsiung Headquarter No. 151, Jin Shan Road, Kaohsiung, Taiwan Tel :+886 7 359 5833 Fax :+886 7 359 5822 E-Mail : anv@anv.com.tw</p> <p>Taipei Office No. 166, Fu Xing 3rd Street, Taishan Dist., New Taipei City, Taiwan Tel :+886 2 2296 3133 Fax :+886 2 2296 3233 E-Mail : taipei@anv.com.tw</p>	<p>Tainan Office No. 60, Lin Sen Road Sec. 1, Tainan, Taiwan Tel:+886 6 216 0988 Fax:+886 6 216 0388 E-Mail : tainan@anv.com.tw</p> <p>ANV ELECTRIC (HK) LTD Flat 4, 14/F., Block 4, Wai Wah Centre, Shatin, N.T., Hong Kong Tel :+852 2690 2588 Fax :+852 2690 2511 E-Mail : anv@anv.com.hk</p>	<p>Taichung Office No. 532, Wen Hsin Road Sec. 1, Taichung, Taiwan Tel :+886 4 2320 9930 Fax :+886 4 2320 9960 E-Mail : taichung@anv.com.tw</p> <p>ANV ELECTRIC (M) SDN. BHD 25-1, Jalan 1/116B, Kuchai Entrepreneur's Park, Off Jalan Kuchai Lama, 58200 Kuala Lumpur, Malaysia Tel :+60 3 7980 3328 Fax :+60 3 7980 3779 E-Mail : anv@anv.com.my</p>
---	---	---